



The Height Safety Specialist

www.akrobat.com.sg

LANYARDS

AK FA 30 600 15

DOUBLE LANYARD

PRODUCT SPECIFICATIONS

- Double rope 1.5m with 2 big snap hooks & 1 twist lock steel carabiner.
- Double lanyard is a component of personal protective equipment against falls from a height and complies with EN354.
- The lanyard LB 122 is made of ø11mm polyamide kernmantle rope.
- Energy absorbers are a component of personal protection equipment. It is made from polyester webbing. Energy absorber made of 45 mm wide polyamide webbing.



PRODUCT'S HIGHLIGHTS & USER'S BENEFITS

- The double lanyard without the energy absorber is not a fall protection.
- Made in EUROPE

PRODUCT USE

-  CONSTRUCTION / CIVIL ENGINEERING
-  HEAVY INDUSTRY
-  LIGHT INDUSTRY
-  OIL / GAS

PRODUCT RISK

-  WEAR & TEAR

CERTIFICATIONS AND STANDARDS

CE 0082
 EN 355:2002 THE ENERGY ABSORBER IS A COMPONENT OF PERSONAL FALL ARREST EQUIPMENT AND COMPLIES WITH EN355.
 EN 354:2002 FALL ARREST SYSTEM CONSISTED OF ENERGY ABSORBER (COMPLIED WITH EN 355) CONNECTED TO LANYARD (COMPLIED WITH EN 354)

- NOTES:
- THE MAXIMUM LIFETIME OF OUR PRODUCTS IS 10 YEARS FROM THE DATE OF MANUFACTURE
 - THE MAXIMUM TIME OF USE OF OUR PRODUCTS IS 5 YEARS FROM THE DATE OF FIRST USE
 - THE PERIODIC INSPECTION MUST BE CARRIED OUT AT LEAST ONCE EVERY 12 MONTHS OF USE
 - THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT HAS BEEN SUBJECTED TO A MAJOR FALL
 - THE EQUIPMENT MUST BE WITHDRAWN FROM USE WHEN IT FAILS TO PASS INSPECTION
 - IT'S RESTRICTED TO USE THE EQUIPMENT WITHOUT MARKING AND WITHOUT VALID IDENTITY CARD



AKROBAT PTE LTD

53 Ubi Avenue 1 #05-13 Paya Ubi Industrial Park Singapore 408934

Tel : 6744 4235 Fax : 6333 8836

salesup@akrobat.com.sg / www.akrobat.com.sg

